

Key Switch Control Stations

Surface Mount and Post Mount

KEYSWITCH 015



- Surface mount
- Single key switch control
- Center return, tamper-proof
- Open / close
- Exterior use
- Nema 3R, 4, 12 encl.
- Housing Material: cast iron encl.
- Operation Temperature: -18°C to 66°C (0°F to 150°F)
- 2 NO contacts
- Dimensions: 4.1" x 4.4" x 2.6"
- Includes: key switch unit, 2 keys
- Key switches without a stop button should only be used with operators wired for constant-pressure-to-open / close (D1 operating mode)

KEYSWITCH 017



- Surface mount
- Single key switch control
- Center return, tamper-proof
- On / off
- 2 stable positions
- Exterior use
- Nema 3R, 4, 12 encl.
- Housing Material: cast iron encl.
- Operation Temperature: -18°C to 66°C (0°F to 150°F)
- 1 NO contact
- Dimensions: 4.1" x 4.4" x 2.6"
- Includes: key switch unit, 2 keys
- Key switches without a stop button should only be used with operators wired for constant-pressure-to-open / close (D1 operating mode)

KEYSWITCH 050



- Surface mount
- Single key switch control
- On / off
- 2 stable positions
- Exterior use
- Nema 4/12 and 4X encl.
- Housing Material: non-metallic encl.
- Operation Temperature: -25°C to 70°C (-13°F to 158°F)
- 1 NO contact
- Dimensions: 2.68" x 2.68" x 4.15"
- Includes: key switch unit, 2 keys
- Replacement parts order: KEY006

KEYSWITCH 051



- Surface mount
- Single key switch control
- On / off
- 1 NO and 1 NC contacts
- Class I, Div. 1 and 2, Groups C, D / Class I, Zones 1 and 2, Groups IIB, IIA / Class II, Div. 1 and 2, Groups E, F, G / Class III, Nema 7 (C, D) / 9 (E, F, G) Classified Hazardous Locations
- CSA certified / UL listed
- Housing Material: aluminum die-cast encl.
- Dimensions: 5" x 6.13" x 5.08"
- Includes: key switch unit, 2 keys

KEYSWITCH 019



- Surface mount
- Single key switch control
- Open / close with 1-button stop
- Exterior use
- Nema 3R, 4, 12 encl.
- Housing Material: aluminum die-cast encl.
- Operation Temperature: -18°C to 66°C (0°F to 150°F)
- Dimensions: 4.1" x 4.4" x 2.6"
- Includes: key switch unit, 2 keys

KEYSWITCH 034



- Wall, post, pipe or pedestal mount
- Single key switch control
- Open / close
- Exterior / interior use
- Nema 4 encl.
- Housing Material: aluminum die-cast encl.
- 1 momentary NO contact
- Dimensions: 2.75" x 4.5" x 2"
- Includes: key switch unit, cylinder, 2 keys
- Key switches without a stop button should only be used with operators wired for constant-pressure-to-open / close (D1 operating mode)
- Replacement parts order: KEYSWITCH006, KEYSWITCH023, KEYSWITCH041

Key Switch Control Stations

Flush Mount, Components and Accessories

KEYSWITCH 010



- Flush mount
- Single key switch control
- Center return, tamper-proof
- Open / close
- Interior use
- Nema 1 encl.
- Housing Material: steel encl.
- Operation Temperature: -18°C to 66°C (0°F to 150°F)
- NO contact
- Dimensions: 4.75" x 6" x 2.75"
- Includes: key switch unit, mounting screws, 2 keys
- Key switches without a stop button should only be used with operators wired for constant-pressure-to-open / close (D1 operating mode)

KEYSWITCH 006



- Replacement cylinder
- Compatible with: KEYSWITCH034

KEYSWITCH 023



- Replacement switch
- SPST momentary NO contact
- Compatible with: KEYSWITCH034

KEYSWITCH 041



- Replacement switch
- SPST momentary NC contact
- Compatible with: KEYSWITCH034

KEY 006



- Replacement keys (set of 2)
- Exterior / interior use
- Compatible with: STATION079, STATION080, KEYSWITCH050