Push-Button Control Stations

Surface Mount

STATION 001



- Surface mount
- 1-button: Open or open/close command
- 1 NO contact
- Nema 1 enclosure
- Interior use
- Materials: Steel
- Dimensions: 2.38"W x 2.78"H x 1.81"D
- Includes: Control station, hardware
- Stop buttons are not provided on 1-button push-button stations. They should only be used with operators wired for constant-pressure-toopen/close (D1 operating mode)

STATION 081



- Surface mount
- 1-button: Open or open/close command
- 1 NO contact
- Nema 4/12 and 4X enclosure
- Interior/exterior use
- Materials: Polycarbonate
- Dimensions: 2.68"W x 2.68"H x 2.44"D
- Operation Temperature: -25°C to 70°C (-13°F to 158°F)
- Includes: Control station
- Additional NO or NC contacts: order PUSH148, PUSH149
- Stop buttons are not provided on 1-button push-button stations. They should only be used with operators wired for constant-pressure-toopen/close (D1 operating mode)

STATION 010



- Surface mount
- 2-button: Open only and close only command
- 2 NO contacts
- Nema 1 enclosure
- Interior use
- Materials: Steel
- Dimensions: 2.38"W x 4.06"H x 1.81"D
- Includes: Control station, hardware
- Stop buttons are not provided on 2-button push-button stations. They should only be used with operators wired for constant-pressure-toopen/close (D1 operating mode)

STATION 082



- Surface mount
- 2-button: Open only and close only command
- 2 NO contacts
- Nema 4/12 and 4X enclosure
- Interior/exterior use
- Materials: Polycarbonate
- Dimensions: 2.68"W x 4.17"H x 2.44"D
- Operation Temperature: -25°C to 70°C (-13°F to 158°F)
- Includes: Control station
- Additional NO or NC contacts: order PUSH148, PUSH149
- Stop buttons are not provided on 2-button push-button stations. They should only be used with operators wired for constant-pressure-toopen/close (D1 operating mode)

STATION 020



- Surface mount
- 3-button: Open/close/stop command
- 2 NO and 1 NC (stop) contacts
- Nema 1 enclosure
- Interior use
- Materials: Steel
- Dimensions: 2.38"W x 5"H x 1.81"D
- Includes: Control station, hardware kit
- For French version: order STATION084

STATION 078



- Surface mount
- 3-button: Open/close/stop command
- 2 NO and 1 NC (stop) contacts
- Nema 4/12 and 4X enclosure
- Interior/exterior use
- Materials: Polycarbonate
- Dimensions: 2.68"W x 5.35"H x 2.44"D
- Operation Temperature: -25°C to 70°C (-13°F to 158°F)
- Includes: Control station
- Additional NO or NC contacts: order PUSH148, PUSH149
- For French version: order STATION078F



Push-Button Control Stations

Surface Mount

STATION 056



- Surface mount
- 3-button: Open/close/stop command
- 2 NO and 1 NC (stop) contacts
- Nema 3R, 4, 12 enclosure
- Interior/exterior use
- Materials: Aluminum die-cast
- Dimensions: 4.2"W x 4.4"H x 3.25"D
- Includes: Control station

STATION 049



- Surface mount
- 3-button: Open/close/stop command
- 2 NO and 1 NC (stop) contacts
- Class I, Div. 1 and 2, Groups C, D
 Class I, Zones 1 and 2, Groups IIB, IIA
 Class II, Div. 1 and 2, Groups E, F, G
 Class III, Nema 7 (C, D)/9 (E, F, G) for classified hazardous locations
- CSA certified/UL listed
- Materials: Aluminum die-cast
- Operation Temperature: -50°C to 40°C (-58°F to 104°F)
- Dimensions: 3" W x 6.13" H x 4.34" D

STATION 079



- Surface mount
- 3-button: Open/close/stop command, key lock-out
- 2 NO and 1 NC (stop) contacts, 1 NO contact (key)
- Nema 4/12 and 4X enclosure
- Interior/exterior use
- Materials: Polycarbonate
- Operation Temperature: -25°C to 70°C (-13°F to 158°F)
- Dimensions: 2.68"W x 6.54"H x 3.35"D (without key)
- Includes: Control station, 2 keys
- Additional NO or NC contacts: order PUSH148, PUSH149
- Replacement parts: order KEY006

STATION 057



- Surface mount
- 3-button: Open/close/stop command, key lock-out
- 2 NO and 1 NC (stop) contacts, NC contact for the key (in series with the NC contact for stop)
- Nema 3R, 4, 12 enclosure
- Interior/exterior use
- Materials: Aluminum die-cast
- Dimensions: 4.2"W x 4.4"H x 3.25"D (without key)
- Includes: Control station, 2 keys

STATION 050



- Surface mount
- 3-button: Open/close/stop command, key lock-out
- 2 NO and 1 NC (stop) contacts, 1 NO and 1 NC contacts (key)
- Class I, Div. 1 and 2, Groups C, D
 Class I, Zones 1 and 2, Groups IIB, IIA
 Class II, Div. 1 and 2, Groups E, F, G
 Class III, Nema 7 (C, D)/9 (E, F, G) for classified hazardous locations
- CSA certified/UL listed
- Materials: Aluminum die-cast
- Operation Temperature: -50°C to 40°C (-58°F to 104°F)
- Dimensions: 6.5"W x 6.13"H x 5.08"D (without key)
- Includes: Control station, 2 keys

STATION 080



- Surface mount
- 3-button: Open/close/stop command, key lock-out and red pilot light
- 2 NO and 1 NC (stop) contacts, 1 NO contact (key)
- Nema 4/12 and 4X enclosure
- Interior/exterior use
- Materials: Polycarbonate
- Operation Temperature: -25°C to 70°C (-13°F to 158°F)
- Dimensions: 2.68"W x 7.72"H x 3.35"D (without key)
- Includes: Control station, hardware, 2 keys
- Additional NO or NC contacts: order PUSH148, PUSH149
- Replacement parts: order KEY006



Push-Button Control Stations

Surface Mount, Flush Mount, Components and Accessories

STATION 070



- Surface mount
- 1-button: Open only or open/close command, mushroom head (green, 40mm) with spring return
- 1 NO contact
- Nema 4/12 and 4X enclosure
- Interior/exterior use
- Materials: Polycarbonate
- Operation Temperature: -25°C to 70°C (-13°F to 158°F)
- Dimensions: 2.68"W x 2.68"H x 3.5"D
- Includes: Control station
- Additional NO or NC contacts: order PUSH148, PUSH149

STATION 085A



- Surface mount
- 1-button: Emergency-stop, mushroom head (red, 40mm), push/twist to unlock
- 1 NC contact
- Nema 4/12 and 4X enclosure
- Interior/exterior use
- Materials: Polycarbonate
- Operation Temperature: -25°C to 70°C (-13°F to 158°F)
- Dimensions: 2.68"W x 2.68"H x 3.75"D
- Includes: Control station
- Additional NO or NC contacts: order PUSH148, PUSH149
- Push/pull option: order STATION085B

STATION 086



- Flush mount
- 3-button: Open/close/stop command
- 2 NO and 1 NC (stop) contacts
- Nema 1 enclosure
- Interior use
- Materials: Steel (enclosure), aluminum (face plate)
- Dimensions (faceplate): 2.75"W x 4.5"H x 0.38"D
- Dimensions (back box): 2.75"W x 4.25"H x 1.88"D
- Includes: Control station

KEY 006



- Replacement keys (2x)
- Compatible with: STATION079, STATION080, KEYSWITCH050

